

Contact us if you have any issues
or questions at
Sales@ProWatercraftRacing.com
(928) 255-0230



Installation Instructions
General Instructions for any Ride Plate Install

Ride Plate



QR Code takes
you directly to the
Install Video.

*We highly recommend
that you watch the
Install Video before
starting this install.*



Supplied with Kit:

Ride Plate (and hardware
depending on your
model watercraft)

READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION

Installing your ride plate is easy to do. Remove the old ride plate and replace with your new Pro Watercraft plate.

Some general things to be aware of:

- Make sure the bolts line up exactly and go in smoothly. One of the worst things you can do is strip the threaded inserts on your ski.
- Apply silicone adhesive in and around all bolts as well as mounting surfaces for the best seal.
- The ride plate will line up with the intake and hull of your ski. Any debris, hull damage, or hull repairs can change this position.
- First, hand tighten the front bolts then install the remaining rear bolts. You may need to apply pressure to the center of the ride plate to align the holes.
- Do not overtighten the bolts! The bolts should be tightened until snug. Countersunk bolts should sit flush to the ride plate.
- Loctite is highly recommended. The lifetime warranty does not apply to improper installation.
- Because our HFC material naturally flexes while riding, check your ride plate every couple rides and before every season.



When installing the ride plate bolts, loosely install each bolt while pushing up with the ride plate so it sits flat with the mounting points. Then tight each, front first, then back two. If your ski uses 6mm bolt, please beware you can over tighten the bolt past the Flex material. Use loctite and silicone on final install.