

Contact us if you have any issues or questions

[Sales@ProWatercraftRacing.com](mailto:Sales@ProWatercraftRacing.com) or  
[928-255-0230](tel:928-255-0230)



Installation Instructions  
KAWASAKI 440/550 HULL  
EXTENSIONS

PW-01-700

Our installation video is not yet available.



**Tools Needed:**

Drill  
11/64" Drill Bit  
Screw Bit  
Hammer  
Chisel  
Rags , Silicone\*

**Parts Included:**

Hull Extensions  
(8) 1 1/4" Screws

**READ ALL INSTRUCTIONS BEFORE BEGINNING INSTALLATION**

- 1 Remove the old hull caps with the hammer and chisel by hitting them off evenly along the caps' seam edge. **FIG 1**  
*Notes: Using a heat gun helps soften the glue and makes the job much easier.*
- 2 Clean off all glue from the hull.
- 3 Pre-fit the hull extensions to make sure they sit in place and are true with the hull. Tape will help hold them in place.
- 4 Pre-drill the mounting holes with the 11/64" drill bit.
- 5 Remove the hull extensions and clean the hull again.
- 6 Apply a silicone bead along the edge and bolt holes of the hull extensions. Fill the holes in the hull with silicone as well.
- 7 Place extensions onto the hull and screw into place. **FIG 2**  
*Warning: The screws may pull the hull extension out of alignment. The extender should be flush with the hull.*
- 8 Clean off any excess silicone from the hull and allow to dry (~24 hrs). Wipe again when dry.

\* Silicone comes in many forms that will not work. Only use silicone adhesive.

Please leave our products a review! ★★★★★

Send us an email with your review and receive a discount on your next order of PWR products.

FIG 1



FIG 2

